

CON STAR - Especificações técnicas



Description

CON STAR é apropriado particularmente para carregadores compactos e pás telescópicas nas aplicações agroindústrias de levantamento e carga. O pneu é caracterizado por uma tração excelente associada com uma estabilidade extraordinária vertical e horizontal. CON STAR foi realizado com um composto de borracha particularmente resistente a qualquer tipo de corte, que contribui a um ciclo de vida prolongado do pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

Version	INDUSTRIAL
Type	TL
Tyre Size	500/70 - 24 (19.5L - 24)
LI/SS	164 A8

Dimensions US Standard

Usa code	94051731
Section Width (inch)	19.9
Overall Diameter (inch)	51.2
Static Loaded Radius (inch)	22.8
Rolling Circumference (inch)	154.6
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E11-106R-003031

Load capacity (lbs)

mph / psi	58
25	11020

Printed on 26/04/2024 05:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..