

## CRANE SPECIAL - Especificações técnicas



### Description

CRANE SPECIAL é apropriado para guindastes móveis “pick & carry” em terrenos de difícil acesso. O pneu é realizado com um composto de borracha especial que fornece uma elevada estabilidade e duração.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Guindaste móvel

Version	STANDARD
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94040582
Ply Rating	28
Overall Width (inch)	18.2
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	173
Rim Rec	11.25/2.0
TRA Code	E3

Load capacity (lbs)

mph / psi	83
30	14800

Printed on 03/05/2024 18:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..