

## EARTHMAX SR 22 - Especificações técnicas



### Description

EARTHMAX SR 22 (G-2/L-2) é um pneu radial **All Steel** particularmente projetado para motoniveladoras e carregadores que operam em condições inverniais extremas na neve ou no gelo. Os operadores apreciarão a excelente tração e a extraordinária estabilidade garantidas pelo piso do pneu largo e não direcional.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Trator de esteira • Motoniveladora • Carregadora

OTR: Trator de esteira • Motoniveladora • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	161 A8/186 A2

## Dimensions US Standard

Usa code	94040803
Overall Width (inch)	20.7
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	169.9
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
Star Rating	*
TRA Code	G2/L2

## Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-
5	-	-	-	-	-	-	-	-	17600	18200	19300	19800	20900

Printed on 26/04/2024 20:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..