

EARTHMAX SR 22 - Especificações técnicas



Description

EARTHMAX SR 22 (G-2/L-2) é um pneu radial All Steel particularmente projetado para motoniveladoras e carregadores que operam em condições inverniais extremas na neve ou no gelo. Os operadores apreciarão a excelente tração e a extraordinária estabilidade garantidas pelo piso do pneu largo e não direcional.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Trator de esteira • Motoniveladora • Carregadora

OTR: Trator de esteira • Motoniveladora • Carregadora

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 23.5 R 25 |
| LI/SS | 170 A8/195 A2 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94062911 |
| Overall Width (inch) | 24 |
| Overall Diameter (inch) | 63.5 |
| Static Loaded Radius (inch) | 27.9 |
| Rolling Circumference (inch) | 191.5 |
| Rim Rec | 19.50/2.5 |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (lbs)

| mph / psi | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 25 | 6950 | 7850 | 8800 | 9900 | 10700 | 11700 | 12300 | 13200 | - | - | - | - | - |
| 5 | - | - | - | - | - | - | - | - | 22700 | 23400 | 24700 | 25400 | 26800 |

Printed on 26/04/2024 19:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..