

## EARTHMAX SR 30 - Especificações técnicas



### Description

EARTHMAX SR 30 (E-3/L-3) é um pneu radial **All Steel** projetado para a utilização dupla com carregadores ou dumper articulados. Os cintos de aço multicamadas e o desenho rígido em blocos, asseguram tração, estabilidade e duração excelentes. O composto de borracha especial, resistente ao corte, torna a EARTHMAX SR 30 a solução ideal para uma variedade de condições operacionais severas.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/176 A2

## Dimensions US Standard

Usa code	94029112
TMPH	103
Overall Width (inch)	17.6
Overall Diameter (inch)	53
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	158.3
Rim Rec	14.00/1.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	9650	10200	10500	11000	11400	12000
5	13200	13600	14300	14800	15700	-

Printed on 27/04/2024 08:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..