

## EARTHMAX SR 30 - Especificações técnicas



### Description

EARTHMAX SR 30 (E-3/L-3) é um pneu radial **All Steel** projetado para a utilização dupla com carregadores ou dumper articulados. Os cintos de aço multicamadas e o desenho rígido em blocos, asseguram tração, estabilidade e duração excelentes. O composto de borracha especial, resistente ao corte, torna a EARTHMAX SR 30 a solução ideal para uma variedade de condições operacionais severas.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

## Dimensions International Standard

TKPH	230
Overall Width (mm)	689
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	766
Rolling Circumference (mm)	5200
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	-

Printed on 27/04/2024 08:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..