

EARTHMAX SR 32 - Especificações técnicas



Description

EARTHMAX SR 32 é o pneu radial de base larga não direcional para scraper. O pneu é caracterizado por uma carcaça robusta All Steel e um composto devidamente formulado que asseguram uma resistência excelente a cortes e lacerações e durabilidade. Vantagens adicionais são uma grande capacidade de tração e de flutuação também durante condições de serviço pesadas.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Raspador

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	33.25 R 29
LI/SS	209 B

Dimensions International Standard

TKPH	346
Overall Width (mm)	845
Overall Diameter (mm)	2080
Static Loaded Radius (mm)	915
Rolling Circumference (mm)	6250
Rim Rec	27.00/3.5
Rim Alt	26.00/3.5
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	15000	15500	16500	17000	17500	18500

Printed on 06/05/2024 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..