

## EARTHMAX SR 32 - Especificações técnicas



### Description

EARTHMAX SR 32 é o pneu radial de base larga não direcional para scraper. O pneu é caracterizado por uma carcaça robusta All Steel e um composto devidamente formulado que asseguram uma resistência excelente a cortes e lacerações e durabilidade. Vantagens adicionais são uma grande capacidade de tração e de flutuação também durante condições de serviço pesadas.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Raspador

|           |                   |
|-----------|-------------------|
| Version   | STANDARD COMPOUND |
| Type      | TL                |
| Tyre Size | 40.5/75 R 39      |
| LI/SS     | 225 B             |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94069392  |
| TMPH                         | 472       |
| Overall Width (inch)         | 38.8      |
| Overall Diameter (inch)      | 102.8     |
| Static Loaded Radius (inch)  | 45.8      |
| Rolling Circumference (inch) | 312       |
| Rim Rec                      | 32.00/4.5 |
| Star Rating                  | **        |
| TRA Code                     | E3        |

## Load capacity (lbs)

| mph / psi | 58    | 62    | 65    | 69    | 73    | 76    |
|-----------|-------|-------|-------|-------|-------|-------|
| 30        | 52000 | 55100 | 56800 | 60000 | 61500 | 64000 |

Printed on 20/02/2024 23:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..