

## EARTHMAX SR 33 PLUS - Especificações técnicas



### Description

EARTHMAX SR 33 PLUS é um pneu radial especial com desenho por blocos projetado para garantir tração e flutuação excelentes em superfícies macias, arenosas ou lamacentas. A carcaça robusta All Steel destaca-se pela excelente durabilidade e a resistência contra cortes e furos. EARTHMAX SR 33 PLUS proporciona uma ótima estabilidade além de uma propriedade de autolimpagem extraordinária.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Veículo universal

Version	STANDARD
Type	TL
Tyre Size	16.00 R 20
LI/SS	173/170 G

## Dimensions US Standard

Usa code	94064038
Overall Width (inch)	17.6
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	156.5
Rim Rec	11.25
Rim Alt	10.00W, 10.0
ECE	E11-54R-0017916

## Load capacity (lbs)

mph / psi	110
56	14330

Printed on 19/04/2024 01:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..