

EARTHMAX SR 33 - Especificações técnicas



Description

Earthmax SR 33 é um pneu radial para veículos universais. O especial desenho por blocos foi projetado para garantir uma tração excelente em superfícies macias, arenosas ou lamacentas. Earthmax SR 33 proporciona uma ótima estabilidade além de uma propriedade de autolimpagem extraordinária. A carcaça All Steel destaca-se pela excelente durabilidade e a resistência contra cortes e furos.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Veículo universal

Version	STANDARD
Type	TL
Tyre Size	365/80 R 20 (14.5 R 20)
LI/SS	152 K

Dimensions International Standard

Overall Width (mm)	360
Overall Diameter (mm)	1096
Static Loaded Radius (mm)	496
Rolling Circumference (mm)	3318
Rim Rec	11
ECE	E11-54R-0017314

Load capacity (Kg)

km/h / bar	6.20
110	3550

Printed on 18/04/2024 00:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..