

EARTHMAX SR 35 - Especificações técnicas



Description

Earthmax SR 35 é um pneu radial All Steel, dotado de baixo perfil, especialmente projetado para dumper articulados e pás carregadoras. É ideal para operações que exigem uma excelente tração e flutuação. Earthmax SR 35 assegura tanto tração como estabilidade excelentes. Graças à carcaça robusta com cintos em aço, garante uma duração extraordinária para além da resistência contra rasgos e furos.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	650/65 R 25 (25/65 R 25)
LI/SS	193 A2

Dimensions International Standard

Overall Width (mm)	635
Overall Diameter (mm)	1498
Static Loaded Radius (mm)	669
Rolling Circumference (mm)	4493
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
10	10000	10600	10900	11500

Printed on 23/04/2024 07:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..