

EARTHMAX SR 412 - Especificações técnicas



Description

EARTHMAX SR 412 (E-4/L-4) é um pneu All Steel particularmente projetado para dumper articulados, pás carregadoras e escavadoras. O desenho único do piso do pneu com profundidade E-4 assegura uma ótima tração e uma resistência elevada ao calor. Graças à sua carcaça robusta e aos cintos All Steel, EARTHMAX SR 412 é capaz de suportar cargas pesadas e fornece uma estabilidade extraordinária assim como uma ótima resistência aos rasgões e furos. EARTHMAX SR 412 distingue-se pelo ombro de forma quadrada que máxima em contacto com o terreno fornecendo um elevado nível de manobrabilidade.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B

Dimensions US Standard

Usa code	94062836
TMPH	173
Overall Width (inch)	30.1
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	218.2
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	E4
Tread Depth	68

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/06/2025 17:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..