

## EARTHMAX SR 412 - Dados técnicos



### Description

EARTHMAX SR 412 (E-4/L-4) é um pneu All Steel particularmente projetado para dumper articulados, pás carregadoras e escavadoras. O desenho único do piso do pneu com profundidade E-4 assegura uma ótima tração e uma resistência elevada ao calor. Graças á sua carcaça robusta e aos cintos All Steel, EARTHMAX SR 412 é capaz de suportar cargas pesadas e fornece uma estabilidade extraordinária assim como uma ótima resistência aos rasgões e furos. EARTHMAX SR 412 distingue-se pelo ombro de forma quadrada que máxima em contacto com o terreno fornecendo um elevado nível de manobrabilidade.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
29.5 R 25	CUT RESISTANT COMPOUND	E4	**	200 B	25.00/3.5		765	1865	834	5543	TL	252
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E4/L4	**/*	190 B/202 A2	24.00/3.0	22.00/3.0; 25.00/3.0	780	1602	715	4838	TL	229
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E4	**	190 B	24.00/3.0	22.00/3.0; 25.00/3.0	780	1602	715	4838	TL	229
800/65 R 29	CUT RESISTANT COMPOUND	E4/L4	**/*	198 B / 208 A2	27.00/3.0	24.00/3.5 , 25.00/3.5	790	1805	825	5490	TL	206

Printed on 23/04/2024 14:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..