

## EARTHMAX SR 423 - Especificações técnicas



### Description

EARTHMAX SR 423 é um pneu radial All Steel apropriado para uma série de aplicações, inclusive operações nas pedreiras, de transporte e na floresta. O desenho não direcional do piso do pneu assegura uma ótima tração e estabilidade em todo o tipo de terreno. O pneu é ideal para o transporte de carregamentos pesados. A carcaça robusta All Steel destaca-se pela longa resistência ao desgaste e a excelente resistência contra cortes e furos. O piso reforçado e o desenho do ombro contribuem para um ciclo de vida mais prolongado, mesmo em condições de serviço pesado.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Camião basculante

|           |                             |
|-----------|-----------------------------|
| Version   | STANDARD                    |
| Type      | TT                          |
| Tyre Size | 12.00 R 24<br>(325/95 R 24) |
| LI/SS     | 160/156 K                   |

## Dimensions US Standard

|                         |          |
|-------------------------|----------|
| Usa code                | 94062096 |
| Ply Rating              | 20       |
| Overall Width (inch)    | 12.5     |
| Overall Diameter (inch) | 48.9     |
| Rim Rec                 | 8.50     |

## Load capacity (lbs)

|                |      |
|----------------|------|
| mph / psi      | 125  |
| 68 Load Single | 9920 |
| 68 Load Dual   | 8820 |

Printed on 24/04/2024 20:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..