

EARTHMAX SR 431 - Dados técnicos



Description

EARTHMAX SR 431 (E-4) é um pneu radial All Steel especialmente projetado para dumper rígidos que operam em condições extremas, principalmente nas minas a céu aberto e subterrâneas. O desenho não direcional do piso do pneu assegura uma ótima tração e estabilidade. O pneu é caracterizado por uma carcaça robusta All Steel e um composto devidamente formulado que asseguram uma resistência excelente a cortes e lacerações, bem como um ciclo de vida mais prolongado, mesmo em ambientes rochosos, abrasivos e hostis.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | TMPH |
|------------|------------------------------|----------|----------|--------|-------|-----------|---------|------|------|------|-------|------|------|
| 16.00 R 25 | CUT RESISTANT COMPOUND | 94062386 | E4 | ** | 177 B | 11.25/2.0 | | 17.8 | 60.3 | 28.1 | 183 | TL | 114 |
| 18.00 R 25 | CUT RESISTANT COMPOUND | 94060788 | E4 | ** | 185 B | 13.00/2.5 | | 20.5 | 65.4 | 29.9 | 198.4 | TL | 96 |
| 18.00 R 25 | CUT RESISTANT COMPOUND (UMS) | 94070794 | E4 | **** | | 13.00/2.5 | | 20.5 | 65.4 | 29.9 | 198.4 | TL | 0 |

Printed on 19/04/2024 22:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..