

EARTHMAX SR 43 - Especificações técnicas



Description

EARTHMAX SR 43 (L-4) é um pneu radial All Steel especialmente projetado para carregadoras de rodas que operam em condições rochosas extremas, principalmente nas minas subterrâneas. O pneu garante excelentes prestações nas operações de carga e de transporte nas minas de céu aberto, nas pedreiras e no estaleiro de demolição. O desenho único do piso do pneu assegura uma tração e uma estabilidade superiores. Graças à estrutura All Steel, EARTHMAX SR 43 (L-4) assegura uma excelente robustez e resistência a lacerações e furos, bem como um ciclo de vida mais prolongado.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	216 A2

Dimensions US Standard

Usa code	94063291
Overall Width (inch)	30.9
Overall Diameter (inch)	73.8
Static Loaded Radius (inch)	33.3
Rolling Circumference (inch)	222.2
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L4

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	41900	43000	44100	45400	46700	49400

Printed on 25/04/2024 10:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..