

## EARTHMAX SR 44 - Especificações técnicas



### Description

EARTHMAX SR 44 é um pneu radial **All Steel** apropriado para uma série de aplicações, inclusive operações na mina, de transporte e na floresta. O desenho robusto do pneu do piso E-4 assegura uma tração e um conforto excelentes para o operador. EARTHMAX SR 44 (E-4) é capaz de otimizar a produtividade, seja qual for a sua operação.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Camião basculante

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	146/143 G

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	268
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3200
Rim Rec	7.50
Rim Alt	7.0 ; 7.50VM ; 8.0
ECE	E11-54R-0015908

## Load capacity (Kg)

km/h / bar	8.3
90	3000

Printed on 26/04/2024 05:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..