

EARTHMAX SR 45 H2 - Especificações técnicas



Description

EARTHMAX SR 45 H2 é um pneu radial All Steel projectado particularmente para dumper rígidos. O desenho único do piso do pneu, com profundidade E-4, reduz o desgaste e minimiza vibrações e ruídos. EARTHMAX SR 45 H2 é ideal para todas as operações que exigem tração e estabilidade. Graças à estrutura All Steel, o pneu assegura uma excelente resistência a lacerações e furos, bem como um ciclo de vida mais prolongado. Disponível com composto de borracha padrão, resistente aos cortes ou ao calor.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	212 B

Dimensions US Standard

Usa code	94063826
TMPH	298
Overall Width (inch)	26
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.5
Rolling Circumference (inch)	259.7
Rim Rec	17.00/3.5
Rim Alt	---
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	105	109	112	116
30	41900	42500	43000	44100

Printed on 26/04/2024 08:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..