

EARTHMAX SR 45 H2 - Dados técnicos



Description

EARTHMAX SR 45 H2 é um pneu radial All Steel projectado particularmente para dumper rígidos. O desenho único do piso do pneu, com profundidade E-4, reduz o desgaste e minimiza vibrações e ruídos. EARTHMAX SR 45 H2 é ideal para todas as operações que exigem tração e estabilidade. Graças à estrutura All Steel, o pneu assegura uma excelente resistência a lacerações e furos, bem como um ciclo de vida mais prolongado. Disponível com composto de borracha padrão, resistente aos cortes ou ao calor.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	333
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	435
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	435
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	390
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	390

Printed on 26/04/2024 05:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..