

EARTHMAX SR 45 M - Dados técnicos

Description

EARTHMAX SR 45 M é um pneu radial All Steel projetado particularmente para dumper rígidos. EARTHMAX SR 45 M assegura uma ótima tração e é o ideal para operações a realizar em longas distâncias.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido



SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	664	2180	980	6538	TL	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	664	2180	980	6538	TL	435
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	664	2180	980	6538	TL	390

Printed on 25/04/2024 23:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..