EARTHMAX SR 45 PLUS - Especificações técnicas

Description

EARTHMAX SR 45 PLUS é um pneu radial All Steel projetado particularmente para dumper rígidos e é ideal para operações de longo percurso. O desenho do piso do pneu do EARTHMAX SR 45 PLUS minimiza vibrações e ruídos.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dumper Rígido

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	654
Overall Width (mm)	746
Overall Diameter (mm)	2702
Static Loaded Radius (mm)	1214
Rolling Circumference (mm)	8095
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5	5.25	5.5	5.75	6	6.25	6.50	6.75	7
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 09:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..