

EARTHMAX SR 454 - Especificações técnicas



Description

O EARTHMAX SR 454 é um pneu radial integralmente em aço, desenhado para os camiões de mineração basculantes rígidos. O design do piso E-3 exclusivo e a ranhura central especial melhoram a tração lateral e a manobrabilidade em superfícies moles e lamacentas. O pneu foi concebido especialmente para a utilização a velocidades mais altas, a longas distâncias e a temperaturas de funcionamento mais baixas. A construção integralmente em aço com lonas de cima em aço de várias camadas garante a melhor proteção com os choques e a penetração de pedras, melhorando o tempo de atividade e a produtividade. O design quadrado do EARTHMAX SR 454 maximiza o contacto com o solo, proporcionando excelente manobrabilidade e estabilidade e reduzindo as vibrações e o ruído.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	33.00 R 51
LI/SS	235 B

Dimensions US Standard

Usa code	94075713
TMPH	606
Overall Width (inch)	35.4
Overall Diameter (inch)	117.7
Static Loaded Radius (inch)	53.5
Rolling Circumference (inch)	357.7
Rim Rec	24.00/5.0
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	66000	68000	71500	74000	76000	78500	80500	82500	85500

Printed on 26/04/2024 19:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..