

EARTHMAX SR 454 - Especificações técnicas



Description

O EARTHMAX SR 454 é um pneu radial integralmente em aço, desenhado para os camiões de mineração basculantes rígidos. O design do piso E-3 exclusivo e a ranhura central especial melhoram a tração lateral e a manobrabilidade em superfícies moles e lamacentas. O pneu foi concebido especialmente para a utilização a velocidades mais altas, a longas distâncias e a temperaturas de funcionamento mais baixas. A construção integralmente em aço com lonas de cima em aço de várias camadas garante a melhor proteção com os choques e a penetração de pedras, melhorando o tempo de atividade e a produtividade. O design quadrado do EARTHMAX SR 454 maximiza o contacto com o solo, proporcionando excelente manobrabilidade e estabilidade e reduzindo as vibrações e o ruído.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	40.00 R 57
LI/SS	250 B

Dimensions International Standard

TKPH	1201
Overall Width (mm)	1115
Overall Diameter (mm)	3510
Static Loaded Radius (mm)	1583
Rolling Circumference (mm)	10654
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	50000	51500	53000	54500	56000	58000	60000

Printed on 26/04/2024 17:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..