

EARTHMAX SR 454 - Dados técnicos



Description

O EARTHMAX SR 454 é um pneu radial integralmente em aço, desenhado para os camiões de mineração basculantes rígidos. O design do piso E-3 exclusivo e a ranhura central especial melhoram a tração lateral e a manobrabilidade em superfícies moles e lamacentas. O pneu foi concebido especialmente para a utilização a velocidades mais altas, a longas distâncias e a temperaturas de funcionamento mais baixas. A construção integralmente em aço com lonas de cima em aço de várias camadas garante a melhor proteção com os choques e a penetração de pedras, melhorando o tempo de atividade e a produtividade. O design quadrado do EARTHMAX SR 454 maximiza o contacto com o solo, proporcionando excelente manobrabilidade e estabilidade e reduzindo as vibrações e o ruído.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	725
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	640
33.00 R 51	CUT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	884
33.00 R 51	HEAT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1215
33.00 R 51	STANDARD COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1023
40.00 R 57	CUT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1201
40.00 R 57	HEAT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1740
40.00 R 57	STANDARD COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1462

Printed on 26/04/2024 19:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..