

EARTHMAX SR 45 - Especificações técnicas



Description

EARTHMAX SR 45 é um pneu radial All Steel projetado particularmente para dumper rígidos. EARTHMAX SR 45 é o pneu ideal para todas as operações que exigem uma tração elevada.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions International Standard

TKPH	220
Overall Width (mm)	505
Overall Diameter (mm)	1870
Static Loaded Radius (mm)	856
Rolling Circumference (mm)	5608
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Printed on 25/04/2024 19:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..