

EARTHMAX SR 475 - Especificações técnicas



Description

EARTHMAX SR 475 é um pneu radial All Steel particularmente projetado para dumper rígidos. É ideal para operações em ambientes duros e rochosos e para o transporte de longo curso. O desenho único do piso do pneu gera menos calor nos clima quentes e fornece uma tração excelente. A sua carcaça robusta All Steel com cintos de aço proporciona uma elevada estabilidade e uma excelente resistência aos cortes e furos. EARTHMAX SR 475 foi desenvolvido com ombro de forma quadrada para assegurar uma excelente manobrabilidade otimizando o contacto ao solo.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions International Standard

TKPH	355
Overall Width (mm)	654
Overall Diameter (mm)	2160
Static Loaded Radius (mm)	971
Rolling Circumference (mm)	6589
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Printed on 17/04/2024 05:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..