

EARTHMAX SR 484 - Especificações técnicas



Description

O EARTHMAX SR 484 é um pneu radial integralmente em aço, desenhado para os camiões basculantes rígidos para o transporte em minas. Apresenta um design exclusivo do piso E-3, com um composto especial que garante excelente proteção em condições difíceis e rochosas, bem como melhor tração e propriedades fantásticas de autolimpeza. A construção integralmente em aço com lonas de cima em aço de várias camadas permite a melhor proteção com os choques, fadiga e a perfuração das rochas, melhorando o tempo de atividade e aumentando a produtividade. O EARTHMAX SR 484 inclui um design quadrado que maximiza o contacto com o solo, garantindo excelente manobrabilidade e estabilidade. Este pneu da BKT foi concebido especialmente para a utilização a velocidades mais altas e a longas distâncias.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	525
Overall Width (mm)	735
Overall Diameter (mm)	2647
Static Loaded Radius (mm)	1193
Rolling Circumference (mm)	8055
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 26/04/2024 12:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..