

EARTHMAX SR 48 - Especificações técnicas



Description

EARTHMAX SR 48 é um pneu All Steel especialmente desenvolvido e realizado para dumper rígidos. Assegura uma maior tração e uma extraordinária resistência ao desgaste, também nas operações mais difíceis em ambientes rochosos. O pneu é ideal para o transporte de carregamentos pesados. O ombro de forma quadrada protege o flanco de cortes e danos. Earthmax SR 48 mostra uma carcaça robusta All Steel que proporciona uma proteção excepcional contra choques e perfurações de pedras, otimizando a produtividade.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions International Standard

TKPH	310
Overall Width (mm)	665
Overall Diameter (mm)	2180
Static Loaded Radius (mm)	993
Rolling Circumference (mm)	6621
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Printed on 15/08/2024 01:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..