EARTHMAX SR 49 M - Especificações técnicas

Description

EARTHMAX SR 49 M é um pneu All Steel com um desenho não direcional especialmente desenvolvido para carregadores LHD, dumpers de baixo perfil, tratores de esteira e carregadoras de rodas que trabalham em condições severas e ambientes rochosos, principalmente nas minas subterrâneas. EARTHMAX SR 49 M é ideal para operações duras que exigem tração e estabilidade excecionais. O piso do pneu, com uma profundidade L-4 e o composto de borracha com uma fórmula especial UMS (underground mine service) garantem uma maior resistência ao desgaste do piso do pneu, bem como uma resistência excelente contra cortes de rocha e furos.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Trator de esteira • Carregadora LHD • Carregadora • Dumper de baixo perfil

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

Dimensions US Standard

Usa code	94058426
TMPH	151
Overall Width (inch)	30.7
Overall Diameter (inch)	75
Static Loaded Radius (inch)	33.2
Rolling Circumference (inch)	220.5
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E4/L4

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	--

Printed on 26/04/2024 13:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..