

EARTHMAX SR 49 - Dados técnicos



Description

EARTHMAX SR 49 (L-4) é um pneu radial All Steel projetado para carregadores e tratores de esteira, dumpers de baixo perfil e carregadoras LHD. EARTHMAX SR 49 assegura ótimas prestações nas operações exigentes em minas, onde tração e estabilidade excelentes representam um requisito essencial. O pneu destaca-se pelo desenho direcional e pelo composto de borracha especialmente resistente contra os furos para assegurar uma durabilidade excelente.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Trator de esteira • Carregadora LHD • Carregadora • Dumper de baixo perfil

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
35/65 R 33	CUT RESISTANT COMPOUND	L4	***	229 A2	28.00/3.5	--	899	2061	890	6125	TL
35/65 R 33	CUT RESISTANT COMPOUND	E4/L4	****/***		28.00/3.5	--	899	2061	890	6125	TL
35/65 R 33	CUT RESISTANT COMPOUND	L4	**	224 A2	28.00/3.5	--	899	2061	890	6125	TL
35/65 R 33	CUT RESISTANT COMPOUND	E4	****		28.00/3.5	--	899	2061	890	6125	TL
45/65 R 45	CUT RESISTANT COMPOUND	L4	**	245 A2	36.00/4.5		1130	2730	1190	8113	TL

Printed on 04/03/2024 09:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..