

## EARTHMAX SR 50 - Especificações técnicas



### Description

EARTHMAX SR 50 (L-5) é um pneu radial All Steel projetado particularmente para carregadores. A carcaça durável e os cordões de proteção são ideais para as operações mais exigentes. EARTHMAX SR 50 é realizado em composto de borracha especial, resistente aos cortes, que reduz o desgaste, assegurando uma vida mais prolongada ao pneu. Os operadores também vão apreciar a tração excelente associada com a estabilidade e a condução confortáveis.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	216 A2

## Dimensions US Standard

Usa code	94069637
Overall Width (inch)	30.5
Overall Diameter (inch)	74.8
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	225.3
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L5

## Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	41900	43000	44100	45400	46700	49400

Printed on 20/04/2024 16:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..