

EARTHMAX SR 53 - Especificações técnicas



Description

EARTHMAX SR 53 é um pneu radial All Steel projetado particularmente para carregadores, tratores de esteira e dumpers de baixo perfil que operam em condições difíceis, nos ambientes rochosos, incluindo as operações em minas subterrâneas e no estaleiro de demolição. O piso do pneu profundo L-5 e o composto de borracha resistente contra os furos reduzem consideravelmente o desgaste, prolongando a vida do pneu, para além de mostrar tração e estabilidade excelentes.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Trator de esteira • Carregadora • Dumper de baixo perfil

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 45/65 R 45 |
| LI/SS | 250 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 1125 |
| Overall Diameter (mm) | 2730 |
| Static Loaded Radius (mm) | 1211 |
| Rolling Circumference (mm) | 8224 |
| Rim Rec | 36.00/4.5 |
| Star Rating | *** |
| TRA Code | L5 |

Load capacity (Kg)

| km/h / bar | 7.00 | 7.50 | 8.00 |
|------------|-------|-------|-------|
| 10 | 54500 | 56000 | 60000 |

Printed on 26/04/2024 05:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..