

## EARTHMAX SR 55 - Especificações técnicas



### Description

EARTHMAX SR 55 (L-55) é um pneu radial All Steel projetado particularmente para carregadores que operam nas condições mais severas, como nas pedreiras, nas minas e no estaleiro de demolição. Graças ao desenho do piso do pneu extra profundo e liso, EARTHMAX SR 55 é capaz de alcançar piques de produtividade elevados com menores tempos de paragem da máquina. Os operadores das máquinas também vão apreciar estabilidade e tração extraordinárias.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Trator de esteira • Carregadora LHD • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	182 A2

## Dimensions International Standard

Overall Width (mm)	453
Overall Diameter (mm)	1399
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4211
Rim Rec	14.00/1.5
Star Rating	**
TRA Code	L5S

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	7300	7500	7750	8000	8250	8500

Printed on 18/04/2024 09:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..