

EARTHMAX SR 55 - Especificações técnicas



Description

EARTHMAX SR 55 (L-55) é um pneu radial All Steel projetado particularmente para carregadores que operam nas condições mais severas, como nas pedreiras, nas minas e no estaleiro de demolição. Graças ao desenho do piso do pneu extra profundo e liso, EARTHMAX SR 55 é capaz de alcançar piques de produtividade elevados com menores tempos de paragem da máquina. Os operadores das máquinas também vão apreciar estabilidade e tração extraordinárias.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Trator de esteira • Carregadora LHD • Carregadora

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 18.00 R 25 |
| LI/SS | 204 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 513 |
| Overall Diameter (mm) | 1667 |
| Static Loaded Radius (mm) | 733 |
| Rolling Circumference (mm) | 4852 |
| Rim Rec | 13.00/2.5 |
| Star Rating | ** |
| TRA Code | L5S |

Load capacity (Kg)

| km/h / bar | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 | 7.25 | 7.50 | 7.75 | 8.00 | 8.25 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 10 | 12150 | 12500 | 12850 | 13200 | 13600 | 14000 | 14500 | 15000 | 15250 | 15500 | 16000 |

Printed on 15/04/2024 10:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..