

EARTHMAX SR 57 - Especificações técnicas



Description

EARTHMAX SR 57 é um pneu radial All Steel, especialmente projetado para carregadores, tratores de esteira e veículos universais utilizados nas minas subterrâneas. O pneu assegura uma tração superior, estabilidade e conforto em superfícies ásperas e rochosas. O piso do pneu extra profundo L-5, junto com o composto de borracha, com uma fórmula especial UMS (underground mine service), garantem uma maior resistência ao desgaste para além de uma resistência extraordinária contra cortes de rocha e furos.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Trator de esteira • Carregadora LHD • Carregadora

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TT |
| Tyre Size | 10.00 R 20 |

Dimensions International Standard

| | |
|-----------------------|------|
| Overall Width (mm) | 272 |
| Overall Diameter (mm) | 1105 |
| Rim Rec | 7.5 |
| Star Rating | * |
| TRA Code | L5 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 7.00 |
| 6 | 4360 |

Printed on 23/04/2024 18:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..