

## EARTHMAX SR LOADER - Especificações técnicas



### Description

EARTHMAX SR LOADER é um pneu OTR especificamente concebido para operações de carregamento e de terraplanagem, bem como para aplicações de transporte com dumpers articulados. A sua lona de carcaça totalmente em aço, reforçada com lonas de cima de aço de várias camadas e um composto de piso exclusivo, proporciona uma resistência excepcional a furos e situações em que o pneu prende, resultando numa vida útil prolongada. O EARTHMAX SR LOADER apresenta um piso único que proporciona propriedades de autolimpeza de topo e uma excelente tração em vários tipos de terreno.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

## Dimensions US Standard

Usa code	94065608
TMPH	185
Overall Width (inch)	30.2
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.5
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Printed on 19/04/2024 01:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..