

EARTHMAX SR LOADER - Dados técnicos



Description

EARTHMAX SR LOADER é um pneu OTR especificamente concebido para operações de carregamento e de terraplanagem, bem como para aplicações de transporte com dumpers articulados. A sua lona de carcaça totalmente em aço, reforçada com lonas de cima de aço de várias camadas e um composto de piso exclusivo, proporciona uma resistência excepcional a furos e situações em que o pneu prende, resultando numa vida útil prolongada. O EARTHMAX SR LOADER apresenta um piso único que proporciona propriedades de autolimpeza de topo e uma excelente tração em vários tipos de terreno.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
20.5 R 25	CUT RESISTANT COMPOUND	94064250	E3/L3	**/*	177 B/186 A2	17.00/2.0		20.9	58.1	25.6	172.6	TL	116
23.5 R 25	CUT RESISTANT COMPOUND	94060283	E3/L3	**/*	185 B/195 A2	19.50/2.5	--	24.1	63.2	27.8	187.8	TL	137
26.5 R 25	CUT RESISTANT COMPOUND	94064847	E3/L3	**/*	193 B/202 A2	22.00/3.0		26.8	68.3	30	203.9	TL	158
29.5 R 25	CUT RESISTANT COMPOUND	94065608	E3/L3	**/*	200 B/208 A2	25.00/3.5		30.2	73.2	32.2	218.5	TL	185

Printed on 18/04/2024 19:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..