

EM 933 SUPER - Especificações técnicas



Description

O EM 933 SUPER foi especialmente concebido para escavadoras em operações de escavação e carregamento. O desenho excecional da parede lateral com uma nervura saliente permite o contacto próximo entre dois pneus, eliminando a necessidade de um anel de borracha especial para evitar a penetração de pedra. O design único do piso proporciona tração superior em condições de utilização intensiva. Entre as características adicionais do EM 933 SUPER encontram-se um conforto de condução excecional e propriedades de autolimpeza melhoradas.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Escavador

Version	STANDARD
Type	TT
Tyre Size	290/90 - 20
LI/SS	152 B / 168 A2

Dimensions US Standard

Usa code	94070183
Ply Rating	18
Overall Width (inch)	11.6
Overall Diameter (inch)	41.5
Rim Rec	8.00
TRA Code	E2

Load capacity (lbs)

mph / psi	131
5	12350
30	7780

Printed on 24/04/2024 08:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..