EM 933 SUPER - Dados técnicos

Description

O EM 933 SUPER foi especialmente concebido para escavadoras em operações de escavação e carregamento. O desenho excecional da parede lateral com uma nervura saliente permite o contacto próximo entre dois pneus, eliminando a necessidade de um anel de borracha especial para evitar a penetração de pedra. O design único do piso proporciona tração superior em condições de utilização intensiva. Entre as características adicionais do EM 933 SUPER encontram-se um conforto de condução excecional e propriedades de autolimpeza melhoradas.

UM

US Standard

Construction

BIAS

Machinery

Industrial: Escavador

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	Type
290/90 - 20	STANDARD	94070183	E2	152 B / 168 A2	18	8.00		11.6	41.5	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 06:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..