

EM 936 SUPER - Especificações técnicas



Description

EM 936 SUPER foi especialmente desenvolvido para escavadores e levantadores telescópicos nas operações de escavação e carga, bem como nas aplicações de transporte. Graças à sua largura do piso do pneu aumentada de 8-10%, EM 936 SUPER destaca-se pela estabilidade extraordinária e um excelente conforto de condução. O pneu também assegura um conforto elevado na movimentação e fornece uma tração excelente, mesmo em condições de serviço pesado.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Escavador

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	145 B

Dimensions US Standard

Usa code	94061860
Ply Rating	14
Section Width (inch)	10.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	131.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	94
30	6395

Printed on 25/04/2024 21:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..