

EM 936 - Especificações técnicas



Description

EM 936 foi especialmente desenvolvido para escavadores e levantadores telescópicos nas operações de escavação e carga. Além disso, uma medida é especialmente apropriada para motoniveladoras e carregadores nas operações de nivelção, carga e transporte. EM 936 destaca-se pelo extraordinário conforto na condução e pelas melhorias nas propriedades de autolimpagem. O pneu também assegura um conforto elevado na movimentação e fornece uma tração excelente, mesmo em condições de serviço pesado. A sua versão especial foi realizada com uma mistura especial.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Escavador • Levantador telescópico

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions US Standard

Usa code	94005314
Ply Rating	16
Overall Width (inch)	10.8
Overall Diameter (inch)	41.3
Static Loaded Radius (inch)	19.6
Rolling Circumference (inch)	125.2
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	109
30	6610

Printed on 29/11/2023 12:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..