

EM 937 E3 (L) - Especificações técnicas



Description

EM 937 (E-3/L-3) foi particularmente concebido para carregadores e retroscavadoras nas aplicações de escavação e carga, de acordo com a medida. O pneu destaca-se pela excelente durabilidade e a ótima resistência a cortes e rasgões.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Retroscavadora • Carregadora

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 14.00 - 24 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94015368 |
| Ply Rating | 24 |
| Overall Width (inch) | 14.8 |
| Overall Diameter (inch) | 53.9 |
| Static Loaded Radius (inch) | 24.7 |
| Rolling Circumference (inch) | 159.4 |
| Rim Rec | 10.00 W |
| TRA Code | E3/L3 |

Load capacity (lbs)

| mph / psi | 83 | 123 |
|-----------|-------|-------|
| 30 | 11400 | - |
| 5 | - | 20900 |

Printed on 17/04/2024 05:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..