

EM 937 E3 (L) - Especificações técnicas



Description

EM 937 (E-3/L-3) foi particularmente concebido para carregadores e retroescavadoras nas aplicações de escavação e carga, de acordo com a medida. O pneu destaca-se pela excelente durabilidade e a ótima resistência a cortes e rasgões.

UM

International Standard

Construction

✚ BIAS

Machinery

Industrial: Retroescavadora • Carregadora

Version	ARAMID BELTED
Type	TT
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4105
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.75	7.00
40	4765	-
10	-	8500

Printed on 17/04/2024 04:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..