

EM 938 - Dados técnicos



Description

EM 938 foi devidamente projetado para escavadores nos estaleiros de construção de estradas. O pneu foi realizado com um composto especial do piso, particularmente resistente contra cortes e lacerações, enquanto o desenho agressivo do piso assegura uma tração excelente. EM 938 destaca-se pelas suas propriedades extraordinárias de autolimpeza. A carcaça robusta proporciona uma resistência excepcional contra colisões e solavancos, também nas operações de serviço pesado.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Escavador

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
9.00 - 20	STANDARD	94046034	E2	140 B	14	7.0	6.5 ; 7.5	10.1	39.8	18.9	120.9	TT
9.00 - 20	STANDARD	94064625	E2		16	7.0	6.5 ; 7.5	10.1	39.8	18.9	120.9	TT

Printed on 05/12/2023 23:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..