



## EM 939 - Dados técnicos



### Description

EM 939 foi especialmente projetado para escavadoras para aplicações de construção rodoviária. O piso do pneu mais profundo com mais barras assegura um ciclo de vida mais longo do pneu. O desenho especial das barras fornece uma tração excelente tanto na estrada como fora de estrada. O pneu fornece ótima tração lateral, bem como ótimas qualidades de autolimpagem. Foi realizado com um composto de borracha especial que fornece uma elevada resistência a cortes e lacerações, enquanto a carcaça robusta garante uma longa vida operacional.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Escavador

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
10.00 - 20	STANDARD	18	7.5	7.0 ; 8.0	280	1075	TT
9.00 - 20	STANDARD	16	7.0	6.5 ; 7.5	260	1025	TT
9.00 - 20	STANDARD	18	7.0	6.5 ; 7.5	260	1025	TT

Printed on 29/04/2024 12:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..