

## FARM HIGHWAY TOUGH - Especificações técnicas



### Description

FARM HIGHWAY TOUGH é um pneu de alta velocidade, projetado para aplicações de transporte e cultivo de sela com reboques e implementos agrícolas. Proporciona uma elevada capacidade de carga mesmo a velocidades elevadas. Além disso, assegura um longo ciclo de vida do pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Implementos agrícolas • Reboque

Version	STANDARD
Type	TL
Tyre Size	12.5L - 15 FI
LI/SS	134 J

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	317
Overall Diameter (mm)	815
Static Loaded Radius (mm)	362
Rolling Circumference (mm)	2323
Rim Rec	10 LB
ECE	E11-54R-0019049

## Load capacity (Kg)

km/h / bar	6.20
100	2120

Printed on 27/04/2024 05:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..