

## FARM SPECIAL - Especificações técnicas



### Description

FARM SPECIAL é um pneu para tratores, idóneo para operações para trabalhar o terreno. A carcaça robusta garante um elevado nível de resistência aos furos e uma vida operacional mais prolongada, enquanto os ombros arredondados evitam danos ao solo, protegendo as culturas preciosas. FARM SPECIAL destaca-se pelo seu único desenho do piso do pneu com elementos mud breaker que quebram a lama, otimizando as propriedades de autolimpagem. Além disso, a dupla angulação dos blocos assegura uma ótima tração com menos deslize.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Trator

Version	STANDARD
Type	TT
Tyre Size	12.4 - 24
LI/SS	121 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	320
Overall Diameter (mm)	1155
Static Loaded Radius (mm)	534
Rolling Circumference (mm)	3504
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-005529
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.30
30	1450

Printed on 25/04/2024 23:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..