

FARM SPECIAL - Especificações técnicas



Description

FARM SPECIAL é um pneu para tratores, idóneo para operações para trabalhar o terreno. A carcaça robusta garante um elevado nível de resistência aos furos e uma vida operacional mais prolongada, enquanto os ombros arredondados evitam danos ao solo, protegendo as culturas preciosas. FARM SPECIAL destaca-se pelo seu único desenho do piso do pneu com elementos mud breaker que quebram a lama, otimizando as propriedades de autolimpagem. Além disso, a dupla angulação dos blocos assegura uma ótima tração com menos deslize.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Trator

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 13.6 - 28 |
| LI/SS | 122 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94060801 |
| Ply Rating | 8 |
| Section Width (inch) | 13.8 |
| Overall Diameter (inch) | 51.6 |
| Static Loaded Radius (inch) | 24 |
| Rolling Circumference (inch) | 156.9 |
| Rim Rec | W 12 |
| Rim Alt | W 11 |
| ECE | E11-106R-005534 |
| TRA Code | R1 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 28 |
| 25 | 3300 |

Printed on 25/04/2024 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..