

FL 252 - Especificações técnicas



Description

FL 252 é um pneu apropriado para aplicações de recolha da palha com ancinhos recolhedores giratórios e viradores e juntadores de fardos, bem como nas operações logísticas com empilhadores. O pneu garante uma duração excelente, enquanto o desenho específico do piso assegura máxima estabilidade durante as operações de elevação.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Ancinho rotativo

Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	7.00 - 12

Dimensions International Standard

Ply Rating	14
Section Width (mm)	192
Overall Diameter (mm)	683
Rim Rec	5.00 S

Load capacity (Kg)

	km/h / bar	9.00
25 LOAD WHEEL		2755
25 STEER WHEEL		2120
10 OTHER VEHICLES		2755
25 OTHER VEHICLES		2120
STATIC SIDE LOADER		3200

Printed on 23/04/2024 08:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..