

## FL 252 - Especificações técnicas



### Description

FL 252 é um pneu apropriado para aplicações de recolha da palha com ancinhos recolhedores giratórios e viradores e juntadores de fardos, bem como nas operações logísticas com empilhadores. O pneu garante uma duração excelente, enquanto o desenho específico do piso assegura máxima estabilidade durante as operações de elevação.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Ancinho rotativo

Industrial: Empilhador

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

## Dimensions US Standard

Usa code	94006939
Ply Rating	14
Section Width (inch)	9.4
Overall Diameter (inch)	33.7
Rim Rec	6.50
Rim Alt	7.0

## Load capacity (lbs)

mph / psi	116
15 LOAD WHEEL	9315
15 STEER WHEEL	7165
5 OTHER VEHICLES	9315
15 OTHER VEHICLES	7165
STATIC SIDE LOADER	10825

Printed on 23/04/2024 09:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..